

## PRODUCT SHEET - POWER SUPPLY FROM MILLETEKNIK

### NEO Battery backup with more alarm functions

#### NEO FLX L



NEO FLX L can be mounted on a wall or in a 19" rack.

### NEO - Name, article number and e-number

Name	Article number	E-number (SV)
NEO 24V 15A FLX L	FL01P10024P150	52 135 43
NEO 24V 25A FLX L	FL01P10024P250	52 135 44

### Description

Primary switched battery backup, 24 V, 15 A, with room for two 45 Ah batteries.

Primary switched battery backup, 24 V, 25 A, with room for two 45 Ah batteries.

### Area of use

NEO supplies power to access systems, alarm systems or other security products in a building that are powered by 24 V DC. The rectifier in the power supply converts 230 V DC down to 24 V DC.

Batteries drive, for example, the access system, when the power grid goes down.

Long life, energy efficient and support is available if something goes wrong, now or in 10 years.

### Voltage, current and power

Mains voltage: 230 V AC - 240 V AC, 47 Hz - 63 Hz.

Voltage out: 27.3 VDC, (24 V).

Charging current: 4 A.

Power outlet: 10 A. 15 A. 25 A.

### Load outputs

Two load outputs.

### Fuses

Mains fuse: 2.5 A. 4 A.

Load securing: 15 A. 25 A.

Battery fuse: (16 A) and 30 A automatic fuse.

### Battery and battery type

Two 45 Ah or two 28 Ah batteries.

Battery type: 12 V, AGM lead-acid battery, maintenance-free. Batteries not included.

### Backup operating time on batteries

The reserve operating time in battery operation depends on how large a load is connected to the power supply. If the load varies, as with frequent opening of door locks, the time that batteries can continue to power the security system decreases. To get an estimate of reserve operating times see: [www.milletechnik.se/Manualer/FaQ/Reservdrifttider/](http://www.milletechnik.se/Manualer/FaQ/Reservdrifttider/)

### Enclosure

Sheet metal cabinet for wall mounting or in a 19" rack cabinet (10 HE). Powder-coated black. Four cable entries on the top and knockout holes on the back. Cable tie holder in enclosure. Lockable, two keys included.

Dimensions, height x width x depth	Built-in fan	IP class
444 x 437 x 212 mm	Yes	IP32

### Weight

Name	Net weight	Weight incl. packaging
Battery backup NEO 24V15A FLX L	15 kg	16 kg
Battery backup NEO 24V25A FLX L	16 kg	17 kg

### Installation requirements

The device is intended for fixed installation. The unit must be installed indoors, environmental class 1, ambient temperature: +5°C to +40°C. Recommended ambient temperature is +15°C to +25°C (for optimal battery life).

### Requirements that the product meets

EMC:	EMC Directive 2014 / 30EU
Electricity:	Low voltage directive: 2014/35 / EU
CE:	CE directive according to: 765/2008
Emission:	EN61000-6-: 2001 EN55022: 1998: -A1: 2000, A2: 2003 Klass B, EN61000-3-2: 2001



### Guarantee

The product has a two-year warranty against manufacturing defects. Batteries and wearing parts are not covered by warranty.

### Expandable, options and accessories

The product can be expanded with two pieces: [2+2 Output module](#) or [5 Output module](#) or [10 Output Module](#) or [8 Output control module](#) or [Fire module 4 outputs](#) or [Voltage Converter 24V-12V 2A](#) or [Voltage Converter 24V-12V 6A](#).

### Tamper switch

### Manufacturing, lifespan, environmental impact and recycling

Manufactured by Milleteknik in Partille, Sweden.

The product is designed and constructed for a long service life, which reduces the environmental impact. The life of the product (except wearing parts) depends on, among other things, environmental factors, mainly ambient temperature, unforeseen load on components such as lightning strikes, external impact, handling errors, etc. Products are recycled, simply because they are modular, by being left at the nearest recycling station or sent back to the manufacturer.<sup>1</sup>Contact your distributor for more information.

### Link to the latest information

Products and software are subject to updates, you will always find the latest information on our website.

### NEO

### About this information

All information is published subject to possible errors. This document is updated without notice.

<sup>1</sup>Costs incurred in connection with recycling are not reimbursed.