

PRODUCT SHEET - POWER SUPPLY FROM MILLETEKNIK

EN54-4 Certified / SBF110:8 Approved battery backup

Figure 1. EN54 24V 25A 2U / EN54 48V 13A 2U



The unit is mounted in a 19" rack.

Name, article number, e-number and certificate number

Table 1. Name, article number, e-number and certificate number.

Name	Article number	E-number
EN54 24V 25A 2U	2U01R10024P250-EN54	52 135 56

Technical description

EN54 power supplies fire alarms with 48 V DC or 24 V DC. The rectifier in the power supply converts 230 V AC down to 48 V DC or 24 V DC and powers all important parts of the fire alarm system. EN54 power supply is certified for use in safety installations that must comply with EN54-4 and/or be approved for SBF 110:8.

Batteries, for example, drive the access system further when the power grid goes down.

Table 2. Quick Facts

Quick Facts	
Supply voltage (V)	[sv] 230 V AC - 240 V AC, 47 Hz- 63 Hz
Voltage out (V)	[sv] 27,3 V DC, (24 V)
Current output (A), max load current output.	[sv] 25 A
Batteries ^a	4 x 150 Ah Front-loaded.

^a Recommended. If batteries are included, it is indicated, otherwise batteries are ordered separately

Areas of application

Table 3. [sv] Användningsområden

Areas of application	Yes	No
Fire alarm	✓	
EN54-4 approved fire alarm systems.	✓	
SBF 110:8, SBSC approved fire alarm system.	✓	
PowerWatch compatible	✓	

Electronics

Table 4. [sv] Elektriska data

[sv] Elektriska data	
[sv] Matningsspänning	[sv] 230 V AC - 240 V AC, 47 Hz- 63 Hz
[sv] Laddström	[sv] Beroende på strömuttag.
[sv] Verkningsgrad ^a	[sv] 89%
[sv] Standbyförbrukning	[sv] 6,98 W
[sv] Spänning ut ^b	[sv] 27,3 V DC, (24 V)
[sv] Ström (A) ^c	[sv] 25 A

^aVid nominell last.

^bGäller även i batteridrift.

^cStrömuttag/last anges som max, normalt strömuttag skall vara 80% av max.

Table 5. Electrical data

Electrical data	
Mains fuse	4 A.
Load fuses	25 A.

Table 6. Printed circuit boards and Internal power consumption

Circuit Boards	Internal power consumption (during battery operation)	Other. info
1HE 24V	270 mA	

Load outputs

Table 7. Load outputs

Load outputs	
Number of load outputs	2

Table 8. Total maximum load and recommended load.

Model	Recommended total load (80%) ^a .
25A	20A

^aTypically, 70-80% of the maximum load is recommended in continuous operation, depending on the thermal margins of the product.

Alarm and protection

Table 9. Number of relay on which alarm can be given

Number of Relays	Alarm on switching relay? ^a
2	✓

^aRelay, alternating potential-free contacts.Ending CO/NO.

Table 10. [sv] Larm

[sv] Larm	[sv] Ja	[sv] Nej
[sv] Åldrat batteri	✓	
[sv] Laddarfel, över-/underspänning	✓	
[sv] Nätavbrottslarm	✓	
[sv] Nätavbrottslarm, 10 sek fördröjning	[sv] ✓	
[sv] Summalarm, temperaturfel (över/ under gränsvärde), säkringsfel: lastsäkring utlöst, batterisäkring utlöst, säkring i externt kort med lastutgångar, jordfel (D-Sub), signalfel (D-Sub), fel eller saknad temperaturgivare (intern eller extern) samt fläktfel.	✓	
[sv] Systemfel	✓	

Table 11. Alarm and protection

Alarm and protection	Yes	No
Battery charge protection/controlled charging ^a	4.5A.	
Deep discharge protection, see Battery [2] ^b	✓	
Overload Protection/Surge Protection	✓	
Over-temperature protection	✓	
Short circuit protection	✓	
[sv] Felövervakning av batteri	✓	
[sv] Nätaggregatsfelövervakning	✓	
[sv] Säkringsskydd	✓	
[sv] Systemövervakning / självtest	✓	
[sv] Underspanningsskydd / låg systemspänning	✓	

^aControlled charging protects and extends battery life.

^bWhen the deep discharge protection is activated, the device turns off and the LED goes out.

Communication and Indications

Table 12. Communication and Indications

Communication and Indications	Yes	No	Other. info.
Communication	✓		
Alarm to subcentral	✓		
PowerWatch ^a	✓		
Indicators/LEDs	✓		LED displays information and alarms on circuit boards and on the outside of the housing.

^aPowerWatch consists of a cable and software, it is ordered separately.

Battery

Table 13. Technical data - Batteries

Battery	
Recommended Batteries ^a	4 x 150 Ah Front-loaded.
Battery type	Maintenance-free AGM (lead-acid) batteries.
Deep discharge protection	Activates when the system voltage drops below about 20 V DC.

^aIf batteries are included, it is indicated, otherwise batteries are ordered separately.

Enclosure and Mechanics

Table 14. Enclosure and Mechanics

Enclosure and Mechanics	
Enclosure	
IP class	IP20
Material	Powder coated sheet metal.
Colour	Black
Height units	3
Cable grommets	
Fan in enclosure	

Dimensions, weight and packaging information

Table 15. Dimensions

Dimensions, (WxHxD).	Dimensions with packaging ^a .
88 x 244 x 280 mm	110 x 440 x 240mm

^aDimensions (WxHxD) of product and packaging may differ, this is because the product may be oriented differently in the package.

Table 16. Weight

Net weight	Weight with packaging
8 kg	8.3 kg

Table 17. Packaging

Packaging	
Packaging	Cardboard and impact protection in cardboard.
Quantity in pack	1 pc.
Packaging Type (GS1 T0137)	BX box.
Conditions EUR pallet	EUR pallets may not be stacked during transport or storage. Stacking may result in damage to product and packaging

Packaging	
Transport environment	The product must be protected from condensation and direct precipitation during transportation.
Transport temperature (without battery)	-30 °C to +70 °C
Storage environment	Dry indoor environment, protected from condensation. Relative humidity: max 95%, non-condensing
Storage temperature without batteries	-20 °C to +60 °C

Assembly, installation and eligibility requirements

Table 18. Fitting

Fitting	[sv] Ja	[sv] Nej
19" rack.	✓	
Wall.	✓	

Table 19. Installation

Installation	Yes	No	Other. info
Fixed installation.	✓		

Backup operating time on batteries

The reserve operating time in battery operation depends on how large a load is connected to the power supply. If the load varies, as with frequent opening of door locks, the time that batteries can continue to power the security system decreases. To get an estimate of reserve operating times see: www.milleteknik.se/Manualer/FaQ/Reservdrifttider/

Operation and maintenance

Table 20. Operation

Operation	Data	Other. info
Environment	Indoor environmental class 1.	
Operating temperature (recommended)	+15°C to +25°C	For the best battery life. Higher temperatures significantly shorten the life of the batteries.
Operating temperature (permissible) ^a .	+5°C to +40°C	Class 1 according to EN 50131-6/ EN 60839-11
Load, power supply	80%	Average load shall not exceed 80% of the rated capacity of the power supply.
Ventilation, in front and behind the enclosure.	100 mm	Ventilation openings must not be blocked or covered.

^aSpecifies the permissible ambient temperature range in which the product can operate without damage. See also table on battery life.

Table 21. Maintenance

Yes	No	Interval	Other. info
✓		Annually	Battery terminal voltage must be measured. Ensure that the average load does not exceed 80% of the rated capacity of the power supply.

Certifications and approvals

Table 22. Approved according to

Complies with	Directives
Emissions	EN61000-6-2:2001 EN 55022:1998: -A 1:2000, A 2:2003 Class B, EN61000-3-2:2001, EN 55032 (replaces EN 55022)
Immunity	EN61000-6-2:2005, EN61000-4-2, -3, 4, -5, -6, -11 SS-EN 50130-4:2011 Edition 2, EN50131-6
C.E.	CE marking according to (EC) 765/2008
EMC	EMC Directive 2014/30EU
Electric (LVD)	Low Voltage Directive: 2014/35/EU

Table 23. EN54

Approved according to standard	Yes	No



Table 24. Certificates and certificate numbers

Certificate number, SBSC	Designation SBSC
Nos. 18-244	-

Environmental data

Table 25. Environmental data

Environmental data	J/N	Informa ie	Other. in-fo.
Building Product Declaration (BPD)	✓	Yes, see iBvd at www.milleteknik.se .	-
REACH Information Obligation (EC) No 1907/2006	✓	Yes, see the DoC at www.milleteknik.se . The product complies with REACH Regulation (EC) No 1907/2006.	If empty, the product is not covered.
SVHC substances, CAS/EC	✓	Yes, lead, 7439-92-1/231-100-4	For text, see iBvd at www.milleteknik.se . If blank, substance is missing.
Subject to the RoHS Directive, (EU) 2015/863	✓	Yes, see the DoC at www.milleteknik.se	
WEEE 2012/19/EU	✓	The product contains electrical components or wiring and is covered by the WEEE Directive (2012/19/EU).	If empty, the product is not covered. End-of-life products must be returned to a recycling centre

Environmental data	J/N	Informa ie	Other. in-fo.
Battery Regulation (EU) 2023/1542	x		
SCIP No 2008/98/EC	✓	Yes, registered under the EU Waste Directive where applicable, (2008/98/EC).	If empty, no SCIP number is needed.
Conflict minerals (EU) 2017/821	x/ x/ x/ ✓	No=Gold, Tungsten, Tantalum, Cobalt. Yes=Tin	Tin in solders in printed circuit boards purchased through a Swedish supplier.
Contains nanomaterials: EC 1272/2008	x	The product does not contain nanomaterials.	-
Ecodesign 2009/125/EC		Milleteknik's products are intended for professional use and are therefore not directly covered by the Ecodesign Regulation (EU 2019/1782). As some components may be covered, we nevertheless disclose relevant information ^a , where applicable, to provide our customers with confidence in their choice.	
Machine Directive 2006/42/EC		The product is part of electrical systems, is subject to the relevant electrical and safety directives and is not a machine according to the Machinery Directive (2006/42/EC). Will be replaced by Machinery Regulation (EU) 2023/1230, which will apply in 2027.	
The product is designed and constructed for a long service life, which reduces the environmental impact. The life of the product (except wearing parts) depends on, among other things, environmental factors, mainly ambient temperature, unforeseen load on components such as lightning strikes, external impact, handling errors, etc. Products are recycled, simply because they are modular, by being left at the nearest recycling station or sent back to the manufacturer. ^b Contact your distributor for more information.			

^aStandby consumption and power.

^bCosts incurred in connection with recycling are not reimbursed.



Delivery time, warranty and terms

Table 26. Delivery time, warranty and terms

Delivery time, warranty and terms	
Warranty period ^a	<i>[sv] Produkten har fem (5) års garanti mot tillverkningsfel.</i>
Special warranty conditions	The battery backup should be used in conjunction with UPLUS 10+ Design Life batteries. The fan shall be cleaned annually and replaced if necessary. The average load shall not exceed 80% of the rated capacity of the power supply. Ambient temperature shall not exceed 32°C. Batteries and wear parts are not covered by warranty. See also general terms and conditions.

Delivery time, warranty and terms	
General Terms and Conditions	ALEM09 with exceptions, see: www.milleteknik.se/conditions/
Support	Telephone support and email support during the warranty period are free of charge. For spare parts that are not covered by warranty, there is a charge
Delivery and stock	
Delivery time ^b	5 working days. Or as per agreement. Delivery from factory, transportation time is added.

^aIf the device is purchased through a wholesaler or other supplier, other warranty conditions may apply

^bIn the case of larger orders, delivery time increases, acc. to agreement.

Manufacturer and country of origin

Table 27. Manufacturer and country of origin

Manufacturer and origin	
Manufacturer ^a	Milleteknik AB
Customs State. Nos.	85043180
Country of origin	Sweden

^aManufacturer is the trademark indicated on the product, regardless of what is stated in this product sheet.

Contact

Table 28. Contact

Department	
Switchboard	031-340 02 30
Support and technical issues	support@milleteknik.se
Sales	sales@milleteknik.se
WWW	www.milleteknik.se
Address	Ögärdesvägen 8B, 433 30 Partille

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Milleteknik with the associated logo is a trademark of Milleteknik AB.

PowerWatch is a trademark of Milleteknik AB.

Publication date 2026-03-17

[SV] BILAGA

[sv] PowerWatch



Table 29. PowerWatch Ordering Information

Name	Item No.	E-number
PowerWatch	A-OT0000UPG02P2V3P3	52 137 06

[sv] Behörighetskrav, installation

[sv] Krav på behörighet varierar mellan länder. Tabellen sammanfattar nationella krav för fast installation respektive anslutning av utrustning med stickkontakt.

Table 30. Eligibility requirements by country. Applies only to the installation of this product in a fixed network connection

Permission Requirements for Installation	Fixed installation (230 V)	Plug	Other. info
Sweden	✓	x	Fixed installation may be performed by technicians but shall be under the responsibility of a qualified installer. (Electrical Safety Act, SS 436 40 00) Plug may be connected without authorization.
Norway	✓	✓	Requirements for qualified electricians also for equipment with a plug socket in fixed installations. (NEK 400, DSB)
Finland	✓	x	Plug may be connected without authorization. (Tukes, SFS 6000)
Denmark	✓	x	Plug may be connected without authorization. (Safety Board)
Germany	✓	x	All fixed installations require a qualified electrician according to VDE 0100. Plug sockets may be connected without authorization, but only by person with basic electrical knowledge ("Elektrotechnisch unterwiesene Person")

[sv] Referenstabell: miljöklasser enligt EN 50130-5 (som hänvisas till i EN 50131-6)

Table 31. Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Class	Type	Temperature range
Environmental Class 1	Heated indoors (type of office/residence).	+5°C to +40°C
Environmental Class 2	Generally indoors (type warehouses/stairwells, not temperature controlled).	-10°C to +40°C
Environmental class 3	Protected outdoors.	-25°C to +50°C
Environmental class 4	Generally outdoors.	-25°C to +60°C

[sv] Referenstabell: tillverkares angivna livslängd och rekommenderat batteribyte

Table 32. Reference table: manufacturer's stated service life and recommended battery replacement

Battery Type (Design Life) ^a	Battery replacement time in normal operation, +20°C.	Replacement during hot operation, +30°C	Replacement during hot operation, +40°C
3 - 5 years	2 - 3 years	1 - 1.5 years	0.5 - 0.75 years
6 - 9 years	5 - 6 years	2.5 - 3 years	1.2 - 1.5 years
10 - 12 years	6 - 7 years	3 - 3.5 years	1.5 - 1.75 years
15 + years	10 - 12 years	5 - 6 years	2.5 - 3 years

^aValid in case of completely unused battery stored under optimal conditions.

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Milleteknik with the associated logo is a trademark of Milleteknik AB.

PowerWatch is a trademark of Milleteknik AB.

Publication date 2026-03-17