

PRODUCT SHEET

Product image



Product Identification

Table 1. Product designation, Part Number and E-Number

Product designation	Item No.	E-number (SE) (sv)
Pole Mount Kit for UT L	A-CA00000PM02	52 579 24

Technical description

The UT L pole mount provides a stable mounting of the enclosure on round posts. The kit consists of brackets and stainless steel plates that ensure structural stability in outdoor environment. The solution supports posts or mast within the specified diameter range and correctly distributes the load across the enclosure. All components are corrosion resistant and dimensioned for the mechanical requirements of the UT L. This kit contains all the parts required for mounting on a pole or mast

Table 2. Quick Facts

Quick Facts	
Accessories for	Outdoor Enclosures.

Areas of application

Table 3. Areas of application

Areas of application	Yes	No
For outdoor enclosures in the size UT L	✓	
For mounting enclosure on pole	✓	

Enclosure and Mechanics

Table 4. Enclosure and Mechanics

Enclosure and Mechanics	
Type	Optional, does not have enclosure
IP class	IP00
Material	Sheet metal
Colour	Silver Grey/Stainless Steel Sheet

Table 5. The option consists of

Component	Number	Description
Sheet metal rail	2	Load-bearing detail for pole or mast mounting.
U-bolt for pole mounting, M10	2	For mounting on round posts according to the specified diameter range
U-bolt for mast mounting, M8	4	Suitable for truss mast pipe; includes nut and washer
Screw, nut and washers		

Assembly, installation and eligibility requirements

Table 6. Fitting

Fitting	Yes	No
Pole or mast.	✓	

Table 7. Installation

Installation	Yes	No
Fixed installation.	✓	

Dimensions, weight and packaging information

Table 8. Diameter Pole Mount

Bracket	Width	Length	Fits pole diameter
U-bolt for pole mounting	145mm	182mm	90-125 mm
U-bolt for mast mounting	46mm	73mm	20-28mm
Pipe post clamp ^a .	40mm	60mm	50mm

^aRequires accessory nut.

Table 9. Dimensions

Dimensions, (WxHxD).	Dimensions with packaging ^a .
530 x 76 x 1.5mm	Data is missing

^aDimensions (WxHxD) of product and packaging may differ, this is because the product may be oriented differently in the package.

Table 10. Weight

Net weight	Weight with packaging
1.9 kg	2.1 kg

Table 11. Packaging

Packaging	
Packaging	Cardboard and impact protection in cardboard.
Quantity in pack	1 pc.
Packaging Type (GS1 T0137)	BX box.
Conditions EUR pallet	EUR pallets may not be stacked during transport or storage. Stacking may result in damage to product and packaging
Transport environment	The product must be protected from condensation and direct precipitation during transportation.
Storage environment	Dry indoor environment, protected from condensation. Relative humidity: max 95%, non-condensing

Fits

Table 12. Bracket suitable for device

Accessories	OUT S	OUT M	OUT L
Pole Mount: Pole Mount Kit for UT L	x	x	✓ (Included)

Contact

Table 13. Contact

Department	
Switchboard	031-340 02 30
Support and technical issues	support@milleteknik.se
Sales	sales@milleteknik.se
WWW	www.milleteknik.se

Department	
Address	Ögärdesvägen 8B, 433 30 Partille

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Publication date 2026-06-25

COMPLIANCE AND REGULATORY COMPLIANCE

Delivery time, warranty and terms

Table 14. Delivery time, warranty and terms

Delivery time, warranty and terms	
Warranty period ^a :	The product has a two (2) year warranty against manufacturing defects.
Special warranty conditions	See also general terms and conditions.
General Terms and Conditions	ALEM09 with exceptions, see: www.milleteknik.se/conditions/
Support	Telephone support and email support during the warranty period are free of charge. For spare parts that are not covered by warranty, there is a charge
Delivery and stock	
Delivery time ^b :	3 working days. Or as per agreement. Delivery from factory, transportation time is added.

^a If the device is purchased through a wholesaler or other supplier, other warranty conditions may apply

^b In the case of larger orders, delivery time increases, acc. to agreement.

Operation and maintenance

Table 15. Operation

Operation	Data	Other. info
Environment	Outdoor Class 3.	

Table 16. Maintenance

Yes	No	Interval	Other. info
	✓		Maintenance-free.

Certifications and approvals

Table 17. Approved according to

Complies with	Directives
C.E.	CE marking according to (EC) 765/2008

Environmental data

Table 18. Environmental data

Environmental data	J/N	Informa ie	Other. info.
Building Product Declaration (BPD)	✓	Yes, see iBvd at www.milleteknik.se .	-
REACH Information Obligation (EC) No 1907/2006			If empty, the product is not covered.
SVHC substances, CAS/EC			For text, see iBvd at www.milleteknik.se . If blank, substance is missing.
Subject to the RoHS Directive, (EU) 2015/863			Mechanical parts are covered if they are part of a RoHS mandatory product

Environmental data	J/N	Informa ie	Other. info.
WEEE 2012/19/EU			If empty, the product is not covered. End-of-life products must be returned to a recycling centre
Battery Regulation (EU) 2023/1542	X		
SCIP No 2008/98/EC			If empty, no SCIP number is needed.
Conflict minerals (EU) 2017/821	X/X/X/X/ X	No=Gold, Tungsten, Tantalum, Cobalt, Tin.	
Contains nanomaterials: EC 1272/2008	X	The product does not contain nanomaterials.	
Ecodesign 2009/125/EC			Milleteknik's products are intended for professional use and are therefore not directly covered by the Ecodesign Regulation (EU 2019/1782). As some components may be covered, we nevertheless disclose relevant information ^a , where applicable, to provide our customers with confidence in their choice.
Machine Directive 2006/42/EC			The product is part of electrical systems, is subject to the relevant electrical and safety directives and is not a machine according to the Machinery Directive (2006/42/EC). Will be replaced by Machinery Regulation (EU) 2023/1230, which will apply in 2027.
The product is designed for a long service life, which reduces the environmental impact. End-of-life products are handed over to the nearest recycling centre.			

^a Standby consumption and power.



Manufacturer and country of origin

Table 19. Manufacturer and country of origin

Manufacturer ^a :	Milleteknik AB
Country of origin	Sweden

^a Manufacturer is the trademark indicated on the product, regardless of what is stated in this product sheet.

APPENDIX

Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Table 20. Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Class	Type	Temperature range
Environmental Class 1	Heated indoors (type of office/residence).	+5°C to +40°C
Environmental Class 2	Generally indoors (type warehouses/stairwells, not temperature controlled).	-10°C to +40°C
Environmental class 3	Protected outdoors.	-25°C to +50°C
Environmental class 4	Generally outdoors.	-25°C to +60°C

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Publication date 2026-06-25