

PRODUCT SHEET

Product image



Product Identification

Table 1. Product designation, Part Number and E-Number

Product designation	Item No.	E-number (SE) (sv)
Speaker Mount Kit for UT M	A-CA00000SM01	52 579 78

Technical description

UT M speaker mount provides a stable and secure installation of speakers and audio equipment in an outdoor environment. The kit consists of screw connections and sheet metal parts that ensure high mechanical stability and long service life even in harsh weather conditions. The solution is adapted for mounting loudspeakers and related equipment on the enclosure and enables accurate load distribution and secure attachment. All components are corrosion-resistant and dimensioned to meet the mechanical requirements of the UT M. This kit contains all the parts necessary for a complete and safe installation of speaker systems

Table 2. Quick Facts

Quick Facts	
Accessories for	Outdoor Enclosures.

Areas of application

Table 3. Areas of application

Areas of application	Yes	No
For mounting speakers on outdoor enclosure	✓	

Enclosure and Mechanics

Table 4. Enclosure and Mechanics

Enclosure and Mechanics	
Type	Optional, does not have enclosure
IP class	IP00
Material	
Colour	Silver Grey/Stainless Steel Sheet

Table 5. The option consists of

Component	Number	Description
Fixing plate	1	
Screw, nut and washers		

Assembly, installation and eligibility requirements

Table 6. Fitting

Fitting	Yes	No
Mounted on compatible product	✓	

Table 7. Installation

Installation	Yes	No
Fixed installation.	✓	

Dimensions, weight and packaging information

Table 8. Dimensions

Dimensions, (WxHxD).	Dimensions with packaging ^a .
245 x 70 x 1.25mm	Data is missing

^aDimensions (WxHxD) of product and packaging may differ, this is because the product may be oriented differently in the package.

Table 9. Weight

Net weight	Weight with packaging
0.5 kg	0.7 kg

Table 10. Packaging

Packaging	
Packaging	
Quantity in pack	1 pc.
Packaging Type (GS1 T0137)	BX box.
Conditions EUR pallet	EUR pallets may not be stacked during transport or storage. Stacking may result in damage to product and packaging
Transport environment	The product must be protected from condensation and direct precipitation during transportation.
Storage environment	Dry indoor environment, protected from condensation. Relative humidity: max 95%, non-condensing

The accessories fits in

Table 11. The option fits the following enclosures

Accessories	Enclosure
Speaker Mount Kit for UT M	OUT M

Contact

Table 12. Contact

Department	
Switchboard	031-340 02 30
Support and technical issues	support@milleteknik.se
Sales	sales@milleteknik.se
WWW	www.milleteknik.se
Address	Ögärdesvägen 8B, 433 30 Partille

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Publication date 2026-06-25

COMPLIANCE AND REGULATORY COMPLIANCE

Delivery time, warranty and terms

Table 13. Delivery time, warranty and terms

Delivery time, warranty and terms	
Warranty period ^a .	The product has a two (2) year warranty against manufacturing defects.
Special warranty conditions	See also general terms and conditions.
General Terms and Conditions	ALEM09 with exceptions, see: www.milleteknik.se/conditions/
Support	Telephone support and email support during the warranty period are free of charge. For spare parts that are not covered by warranty, there is a charge
Delivery and stock	
Delivery time ^b .	Or as per agreement. Delivery from factory, transportation time is added.

^aIf the device is purchased through a wholesaler or other supplier, other warranty conditions may apply

^bIn the case of larger orders, delivery time increases, acc. to agreement.

Operation and maintenance

Table 14. Operation

Operation	Data	Other. info
Environment		

Table 15. Maintenance

Yes	No	Interval	Other. info
	✓		Maintenance-free.

Certifications and approvals

Table 16. Approved according to

Complies with	Directives
C.E.	CE marking according to (EC) 765/2008

Environmental data

Table 17. Environmental data

Environmental data	J/N	Informa ie	Other. info.
Building Product Declaration (BPD)	✓	Yes, see iBvd at www.milleteknik.se .	-
REACH Information Obligation (EC) No 1907/2006			If empty, the product is not covered.
SVHC substances, CAS/EC			For text, see iBvd at www.milleteknik.se . If blank, substance is missing.
Subject to the RoHS Directive, (EU) 2015/863			

Environmental data	J/N	Informa ie	Other. info.
WEEE 2012/19/EU			If empty, the product is not covered. End-of-life products must be returned to a recycling centre
Battery Regulation (EU) 2023/1542			
SCIP No 2008/98/EC			If empty, no SCIP number is needed.
Contains nanomaterials: EC 1272/2008	x	The product does not contain nanomaterials.	
Ecodesign 2009/125/EC		Milleteknik's products are intended for professional use and are therefore not directly covered by the Ecodesign Regulation (EU 2019/1782). As some components may be covered, we nevertheless disclose relevant information ^a , where applicable, to provide our customers with confidence in their choice.	
Machine Directive 2006/42/EC		The product is part of electrical systems, is subject to the relevant electrical and safety directives and is not a machine according to the Machinery Directive (2006/42/EC). Will be replaced by Machinery Regulation (EU) 2023/1230, which will apply in 2027.	

^aStandby consumption and power.



Manufacturer and country of origin

Table 18. Manufacturer and country of origin

Manufacturer ^a	
Country of origin	

^aManufacturer is the trademark indicated on the product, regardless of what is stated in this product sheet.

APPENDIX

Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Table 19. Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Class	Type	Temperature range
Environmental Class 1	Heated indoors (type of office/residence).	+5°C to +40°C
Environmental Class 2	Generally indoors (type warehouses/stairwells, not temperature controlled).	-10°C to +40°C
Environmental class 3	Protected outdoors.	-25°C to +50°C
Environmental class 4	Generally outdoors.	-25°C to +60°C

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Publication date 2026-06-25