

PRODUCT SHEET

Technical specifications: Power Supply 24V 3A



Product Identification

Table 1. Power Supply name, part number and e-number.

Product designation	Item No.	E-number (SE)
Power Supply 24V 3A	MI01000024P030	52 574 65

Technical description

The product is used when the need arises to convert 230 V to 12 V or 24 V but backup power in case of power loss is not needed.

Table 2. Quick Facts

Quick Facts	
Supply voltage (V)	230V AC, +/- 10%, 47Hz-63Hz
Voltage out (V)	27.3 V DC, (24 V DC)
Current output (A), max load current output.	1.1 A- 6.5 A

Areas of application

Table 3. Areas of application

Areas of application	Yes	No
Access system (door reader, magnetic lock, electric terminal plate, etc)	✓	
Burglar alarm	✓	

Electrical data

Table 4. Electrical data

Electrical data	
Supply voltage	230V AC, +/- 10%, 47Hz- 63Hz
Standby consumption	<0.5W
Voltage out	27.3 V DC, (24 V DC)
Current (A) ^a .	1.1 A- 6.5 A

^aPower outlet/load is specified as max, normal current output should be 80% of max.

Load outputs

Table 5. Load outputs

Load outputs	
Number of load outputs	! 1

Table 6. Total maximum load and recommended load.

Model	Recommended total load (80%) ^a .
3A	2.4 A

^aTypically, 70-80% of the maximum load is recommended in continuous operation, depending on the thermal margins of the product.

Alarm and protection

Table 7. Alarm and protection

Alarm and protection	Yes	No
Overload Protection/ Surge Protection	✓	
Over-temperature protection	✓	
Short circuit protection	✓	

Enclosure and Mechanics

Table 8. Enclosure and Mechanics

Enclosure and Mechanics	
Type	Universal enclosure for wall
IP class	IP20
Material	Powder coated sheet metal.
Colour	White
Cable grommets	2 pcs
Knockout hole	1 pc. on the back
Lock	✓ 2 keys included
Fan in enclosure	X

Assembly, installation and eligibility requirements

Table 9. Fitting

Fitting	Yes	No
Wall.	✓	

Table 10. Installation

Installation	Yes	No
Fixed installation.	✓	

Dimensions, weight and packaging information

Table 11. Dimensions

Dimensions, (WxHxD).	Dimensions with packaging ^a .
202 x 148 x 62mm	100 x 210 x 155 mm

^aDimensions (WxHxD) of product and packaging may differ, this is because the product may be oriented differently in the package.

Table 12. Weight

Net weight	Weight with packaging
0.9 kg	1 kg

Table 13. Packaging

Packaging	
Packaging	Cardboard and impact protection in cardboard.
Quantity in pack	1 pc.
Packaging Type (GS1 T0137)	BX box.
Conditions EUR pallet	EUR pallets may not be stacked during transport or storage. Stacking may result in damage to product and packaging
Transport environment	The product must be protected from condensation and direct precipitation during transportation.
Transport temperature (without battery)	-30 °C to +70 °C
Storage environment	Dry indoor environment, protected from condensation. Relative humidity: max 95%, non-condensing
Storage temperature without batteries	-20 °C to +60 °C

Contact

Table 14. Contact

Department	
Switchboard	031-340 02 30
Support and technical issues	support@milleteknik.se
Sales	sales@milleteknik.se
WWW	www.milleteknik.se
Address	Ögärdesvägen 8B, 433 30 Partille

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Publication date 2026-07-14

COMPLIANCE AND REGULATORY COMPLIANCE

Delivery time, warranty and terms

Table 15. Delivery time, warranty and terms

Delivery time, warranty and terms	
Warranty period ^a .	The product has a two (2) year warranty against manufacturing defects.
Special warranty conditions	See also general terms and conditions.
General Terms and Conditions	ALEM09 with exceptions, see: www.milleteknik.se/conditions/
Support	Telephone support and email support during the warranty period are free of charge. For spare parts that are not covered by warranty, there is a charge
Delivery and stock	
Delivery time ^b .	3 working days. Or as per agreement. Delivery from factory, transportation time is added.

^aIf the device is purchased through a wholesaler or other supplier, other warranty conditions may apply.

^bIn the case of larger orders, delivery time increases, acc. to agreement.

Operation and maintenance

Table 16. Operation

Operation	Data	Other. info
Environment	Indoor environmental class 1.	
Operating temperature (recommended)	+15°C to +25°C	
Operating temperature (permissible) ^a .	+5°C to +40°C	Class 1 according to EN 50131-6/ EN 60839-11
Load, power supply	80%	Average load shall not exceed 80% of the rated capacity of the power supply.
Ventilation, free distance around the enclosure.	100 mm	Ventilation openings must not be blocked or covered.

^aSpecifies the permissible ambient temperature range in which the product can operate without damage. See also table on battery life.

Table 17. Maintenance

Yes	No	Interval	Other. info
	✓		Maintenance-free.

Certifications and approvals

Table 18. Approved according to

Complies with	Directives
Emissions	EN61000-6-2:2001 EN 55022:1998: -A 1:2000, A 2:2003 Class B, EN61000-3-2:2001, EN 55032 (replaces EN 55022)
Immunity	EN61000-6-2:2005, EN61000-4-2, -3, 4, -5, -6, -11 SS-EN 50130-4:2011 Edition 2, EN50131-6
C.E.	CE marking according to Regulation (EC) No 765/2008
RoHS	RoHS Directive 2011/65/EU, including amendment (EU) 2015/863
EMC	EMC Directive 2014/30/EU
Electric (LVD)	Low Voltage Directive 2014/35/EU

Environmental data

Table 19. Environmental data

Environmental data	J/N	Informație	Other. info.
Building Product Declaration (BPD)	✓	Yes, see iBvd at www.milleteknik.se .	-
REACH Information Obligation (EC) No 1907/2006	✓	Yes, see the DoC at www.milleteknik.se The product complies with REACH Regulation (EC) No 1907/2006.	If empty, the product is not covered.
SVHC substances, CAS/EC	✓	Yes, lead, 7439-92-1/231-100-4	For text, see iBvd at www.milleteknik.se . If blank, substance is missing.
Subject to the RoHS Directive, (EU) 2015/863)	✓	Yes, see the DoC at www.milleteknik.se	
WEEE 2012/19/EU	✓	The product contains electrical components or wiring and is covered by the WEEE Directive (2012/19/EU).	If empty, the product is not covered. End-of-life products must be returned to a recycling centre
Battery Regulation (EU) 2023/1542	X		
SCIP No 2008/98/EC	✓	Yes, registered under the EU Waste Directive where applicable, (2008/98/EC).	If empty, no SCIP number is needed.
Conflict minerals (EU) 2017/821	X/ X/ X/ X/✓	No=Gold, Tungsten, Tantalum, Cobalt. Yes=Tin	Tin in solders in printed circuit boards purchased through a Swedish supplier.
Contains nanomaterials: EC 1272/2008	X	The product does not contain nanomaterials.	

Environ-mental da-ta	J/N	Informație	Other. in-fo.
Ecodesign 2009/125/E C		Milleteknik's products are intended for professional use and are therefore not directly covered by the Ecodesign Regulation (EU 2019/1782). As some components may be covered, we nevertheless disclose relevant information ^a , where applicable, to provide our customers with confidence in their choice.	
Machine Di-rective 2006/42/EC		The product is part of electrical systems, is subject to the relevant electrical and safety directives and is not a machine according to the Machinery Directive (2006/42/EC). Will be replaced by Machinery Regulation (EU) 2023/1230, which will apply in 2027.	
The product is designed and constructed for a long service life, which reduces the environmental impact. The life of the product (except wearing parts) depends on, among other things, environmental factors, mainly ambient temperature, unforeseen load on components such as lightning strikes, external impact, handling errors, etc. Products are recycled, simply because they are modular, by being left at the nearest recycling station or sent back to the manufacturer. ^b Contact your distributor for more information.			

^aStandby consumption and power.

^bCosts incurred in connection with recycling are not reimbursed.



Manufacturer and country of origin

Table 20. Manufacturer and country of origin

Manufacturer ^a	Milleteknik AB
Customs State. Nos.	85044095 ^b
Country of origin	Sweden

^aManufacturer is the trademark indicated on the product, regardless of what is stated in this product sheet.

^bVerify with the Customs Ombud/Customs Service for export/import; alternative classifica-tion 85044055 may become applicable if the product is assessed as a battery charger.

APPENDIX

Eligibility requirements, installation

Eligibility requirements vary between countries. The table summarizes national requirements for fixed installation and connection of equipment with a plug socket, respectively.

Options on the secondary side of the product, such as 12 V, 24 V or 48 V DC, are connected according to the respective instructions. Work on the network connection of the product shall be carried out in accordance with national eligibility requirements

Table 21. Eligibility requirements by country. Applies only to the installation of this product in a fixed network connection

Permis- sion Re- quire- ments for In- stalla- tion	Fixed instal- lation (230 V)	Plug	Other. info
Sweden	✓	X	Fixed installation may be performed by technicians but shall be under the responsibility of a qualified installer. (Electrical Safety Act, SS 436 40 00) Plug may be connected without authorization.
Norway	✓	✓	Requirements for qualified electricians also for equipment with a plug socket in fixed installations. (NEK 400, DSB)
Finland	✓	X	Plug may be connected without authorization. (Tukes, SFS 6000)
Denmark	✓	X	Plug may be connected without authorization. (Safety Board)
Germany	✓	X	All fixed installations require a qualified electrician according to VDE 0100. Plug sockets may be connected without authorization, but only by person with basic electrical knowledge ("Elektrotechnisch unterwiesene Person")

Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Table 22. Reference table: environmental classes according to EN 50130-5 (referred to in EN 50131-6)

Class	Type	Temperature range
Environmental Class 1	Heated indoors (type office/residence).	+5°C to +40°C
Environmental Class 2	Generally indoors (type warehouses/stairwells, not temperature controlled).	-10°C to +40°C
Environmental class 3	Protected outdoors.	-25°C to +50°C
Environmental class 4	Generally outdoors.	-25°C to +60°C

About this information

All information is published subject to possible errors. Information is updated without prior notice.

Publication date 2026-07-14